PROCHEMKO

## PROCHEMKO ALGAE KILLER

# Concentrated cleaner removes green film

- Works effectively
- Works preventatively
- Simple to use
- Time saver

# PROCHEMKO ALGAE KILLER

## ОПИСАНИЕ
For the effective removal and prevention of algae and moss. Usable on windows, windows, roofs, terraces, tile paths, beams, deck, garden furniture, etc.

## ПРЕПОРЪЧИТЕЛНА УПОТРЕБА
It may only be used as an agent to combat green film.
This product may not be used to combat green film hard surfaces and equipment that are near watercourses.
This product is poisonous to fish and other water organisms.
The liquid must be prevented from reaching surface water.

## РАЗХОДНА НОРМА
Ca. 3 – 5 m² pro liter solution.

## КОНСУМАЦИЯ
Consumption is heavily dependent on the surface roughness and fouling.

## НАЧИН НА УПОТРЕБА
Clean the surface, the wet the surfaces to be treated, and allow to soak in for minimally 16 hours.
After the soak-in period, spray off the surface with the help of a brush or sanding pad.
For preventative action, treat the surface again and allow to dry.
Apply the product with a low-pressure spray.
Use Algae Killer Concentrate diluted to a ratio between 1:25 to 1:100 dependent on the degree of fouling of the surface.
Capture contaminated water and prevent it reaching the ground, surface water, or the sewers.

## УСЛОВИЯ ЗА НАНАСЯНЕ
Minimum ambient temperature : 10 °C.
Minimum surface temperature : 10 °C.
Maximum ambient temperature : 30 °C.

## ПОЧИСТВАНЕ НА ОБОРУДВАНЕ И РАЗЛИВИ
Rinse with water immediately after use.

## ЗАБЕЛЕЖКИ
Use Algae Killer Concentrate diluted between 1:25 to 1:100 dependent on the degree of fouling of the surface.
Capture contaminated water and prevent it reaching the ground, surface water, or the sewers.
Remnants of this product should be treated as chemical waste and may not be disposed of together with commercial or household waste.
Treat empty packaging as industrial waste unless well cleaned and dry.
Do not dispose of clean packaging as chemical waste.

## PH
9

## СРОК НА ГОДНОСТ
Can be kept a minimum of 12 months from the date of delivery when stored in a dry environment at a temperature between 0 °C and 30 °C in the unopened original packaging.

**Дата на издаване:** 28/05/2026

**Налични цветове и размери на опаковките:** Моля, вижте съответната продуктова страница на www.rust-oleum.eu, за да се запознаете с актуалните налични цветове и размери на опаковките.

**Отказ от отговорност:** Информацията, съдържаща се в този документ, доколкото ни е известно, е вярна и точна и се предоставя добросъвестно, но без гаранция. Счита се, че потребителят се е уверил самостоятелно в пригодността на нашите продукти за неговата/нейната конкретна цел. При никакви обстоятелства Rust-Oleum Europe не носи отговорност за последващи или случайни щети. Продуктите трябва да се съхраняват, обработват и нанасят при условия, съответстващи на препоръките на Rust-Oleum Europe, подробно описани в последното копие на информационния лист на продукта. Отговорност на потребителите е да се уверят, че разполагат с актуалното копие. Последните копия на информационния лист за продукта са на разположение безплатно и могат да бъдат изтеглени от www.rust-oleum.eu или при запитване до нашия отдел за обслужване на клиенти. Rust-Oleum Europe си запазва правото да променя свойствата на своите продукти без предварително уведомление.

**Rust-Oleum Netherlands B.V.**
Europalaan 9
5232 BC 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

**Tor Coatings Ltd (Rust-Oleum Industrial)**
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

**Rust-Oleum France S.A.S.**
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

**N.V. Martin Mathys S.A.**
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu