



PROCHEMKO ALGAE KILLER

Concentrated cleaner removes green film

- Works effectively
- Works preventatively
- Simple to use
- Time saver

PROCHEMKO ALGAE KILLER

POPIS PRODUKTU (DLOUHÝ)

For the effective removal and prevention of algae and moss. Usable on windows, windows, roofs, terraces, tile paths, beams, deck, garden furniture, etc.

DOPORUČENÉ POUŽITÍ

It may only be used as an agent to combat green film.
This product may not be used to combat green film hard surfaces and equipment that are near watercourses.
This product is poisonous to fish and other water organisms.
The liquid must be prevented from reaching surface water.

TEORETICKÁ SPOTŘEBA

Ca. 3 – 5 m² pro liter solution.

PRAKTICKÁ SPOTŘEBA

Consumption is heavily dependent on the surface roughness and fouling.

NÁVOD K POUŽITÍ

Clean the surface, the wet the surfaces to be treated, and allow to soak in for minimally 16 hours.
After the soak-in period, spray off the surface with the help of a brush or sanding pad.
For preventative action, treat the surface again and allow to dry.
Apply the product with a low-pressure spray.
Use Algae Killer Concentrate diluted to a ratio between 1:25 to 1:100 dependent on the degree of fouling of the surface.
Capture contaminated water and prevent it reaching the ground, surface water, or the sewers.

PODMÍNKY POUŽITÍ

Minimum ambient temperature : 10 °C.
Minimum surface temperature : 10 °C.
Maximum ambient temperature : 30 °C.

ČIŠTĚNÍ ZAŘÍZENÍ / ROZLITÍ

Rinse with water immediately after use.

POZNÁMKY

Use Algae Killer Concentrate diluted between 1:25 to 1:100 dependent on the degree of fouling of the surface.
Capture contaminated water and prevent it reaching the ground, surface water, or the sewers.
Remnants of this product should be treated as chemical waste and may not be disposed of together with commercial or household waste.
Treat empty packaging as industrial waste unless well cleaned and dry.
Do not dispose of clean packaging as chemical waste.

PH

9

DOBA POUŽITELNOSTI

Can be kept a minimum of 12 months from the date of delivery when stored in a dry environment at a temperature between 0 °C and 30 °C in the unopened original packaging.

last_updated: 05/02/2025

footer_data_colors_pack_sizes: footer_data_colors_pack_sizes.value

footer_data_disclaimer: footer_data_disclaimer.value

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu