



## PROCHEMKO ALGAE KILLER

# Concentrated cleaner removes green film

- Works effectively
- Works preventatively
- Simple to use
- Time saver

# PROCHEMKO ALGAE KILLER

## DESCRIPTION

For the effective removal and prevention of algae and moss. Usable on windows, windows, roofs, terraces, tile paths, beams, deck, garden furniture, etc.

## RECOMMENDED USE

It may only be used as an agent to combat green film.

This product may not be used to combat green film hard surfaces and equipment that are near watercourses.

This product is poisonous to fish and other water organisms.

The liquid must be prevented from reaching surface water.

## THEORETICAL CONSUMPTION

Ca. 3 – 5 m<sup>2</sup> pro liter solution.

## PRACTICAL CONSUMPTION

Consumption is heavily dependent on the surface roughness and fouling.

## DIRECTIONS FOR USE

Clean the surface, the wet the surfaces to be treated, and allow to soak in for minimally 16 hours.

After the soak-in period, spray off the surface with the help of a brush or sanding pad.

For preventative action, treat the surface again and allow to dry.

Apply the product with a low-pressure spray.

Use Algae Killer Concentrate diluted to a ratio between 1:25 to 1:100 dependent on the degree of fouling of the surface.

Capture contaminated water and prevent it reaching the ground, surface water, or the sewers.

## APPLICATION CONDITIONS

Minimum ambient temperature : 10 °C.

Minimum surface temperature : 10 °C.

Maximum ambient temperature : 30 °C.

## CLEANING OF EQUIPMENT / SPILLS

Rinse with water immediately after use.

## REMARKS

Use Algae Killer Concentrate diluted between 1:25 to 1:100 dependent on the degree of fouling of the surface.

Capture contaminated water and prevent it reaching the ground, surface water, or the sewers.

Remnants of this product should be treated as chemical waste and may not be disposed of together with commercial or household waste.

Treat empty packaging as industrial waste unless well cleaned and dry.

Do not dispose of clean packaging as chemical waste.

## PH

9

## SHELF LIFE

Can be kept a minimum of 12 months from the date of delivery when stored in a dry environment at a temperature between 0 °C and 30 °C in the unopened original packaging.

Date issued: 05/02/2025

**Available colours & pack sizes:** Please refer to the respective product page on [www.rust-oleum.eu](http://www.rust-oleum.eu) for an overview of actual available colours and pack sizes.

**Disclaimer:** The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from [www.rust-oleum.eu](http://www.rust-oleum.eu) or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T : +31 (0) 165 593 636  
F : +31 (0) 165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T : +44 (0)1914 113 146  
F : +44 (0)1914 113 147  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T : +33(0) 130 40 00 44  
F : +33(0) 130 40 99 80  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T : +32 (0) 13 460 200  
F : +32 (0) 13 460 201  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)