



CONCENTRATED WALLPAPER STRIPPER

Quickly and easily removes wallpaper

- Easy to apply
- Short absorption time
- Dissolves glue
- Concentrated

CONCENTRATED WALLPAPER STRIPPER

DESCRIPTION

For the quick removal of wallpaper, posters, etc.
Penetrates deep into the adhesive and dissolves it. Suitable for all surfaces.

RECOMMENDED USE

Used to easily remove all wallpaper on all surfaces.
Scrape off vinyl or strip vinyl layer.

THEORETICAL CONSUMPTION

10 - 20 m² per liter of undiluted product.

DIRECTIONS FOR USE

Cover floor covering, skirting, and woodwork.
Place watertight protection on power sockets, switches, and other electrically conductive items.
Dilute Behangbikker with water to a ratio of 1:5 and apply evenly on the surface using a wide brush, or low-pressure hand spray.
Allow Behangbikker solution to soak in for 15 to 30 minutes and use a spatula to remove the softened layers. When dried out, apply the solution again.
With multiple layers, repeat the treatment.

APPLICATION CONDITIONS

It is not necessary to take any special measures for indoor conditions.

CLEANING OF EQUIPMENT / SPILLS

Rinse with clean water immediately after use.

REMARKS

Dispose of remaining product, empty packaging, and removed wallpaper as household waste in accordance with the local regulations and legal requirements.

PH

11,40

SHELF LIFE

Can be kept for a minimum of 24 months when stored in a dry, cool, and frost-free environment in the unopened original packaging.

Date issued: 05/02/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu