PROCHEMKO

B-WAX

Sacrificial anti-graffiti coating

- Suitable for a wide variety of surfaces, porous, or smooth
- Virtually invisible
- Weather resistant
- Water permeable

B-WAX

ОПИСАНИЕ
It is a virtually invisible anti-graffiti and anti-poster coating based on natural waxes for all surfaces resistant to water from minimally 60 °C.

ПРЕПОРЪЧИТЕЛНА УПОТРЕБА
This is a sacrificial anti-graffiti coating for all mineral construction materials, natural stone, and other façade cladding.

ТЕХНИЧЕСКИ ДАННИ
Плътност (г/см³):	1,02 kg/l
Гланцово ниво:	Атлас

ВРЕМЕ ЗА СУШЕНЕ ДО 20º C/RH 50%
Сух на допир:	N/A
Готов за повторно нанасяне:	N/A
group_dry_40_full_cure:	N/A

РАЗХОДНА НОРМА
3 – 5 m² / l in a 2 layer system.

НАЧИН НА УПОТРЕБА
Clean the surface with an appropriate Prochemko façade cleaning agent and allow the surface to dry.
Remove previously applied graffiti remover using Topper or Removex Green.
Spray off with water under high pressure.
Apply B-Wax on a dry surface using a brush, roller, or low-pressure hand spray.
For optimal results with a standard system, apply a second layer crosswise after a two-hour drying time.
Remove graffiti using high-pressure hot water minimally at 80 °C. Then apply the new system.
First apply Prochemko Grease Cleaner Foam to old layers of B-Wax. Then allow it to soak in for a few minutes. Now wipe all of it with a hard brush and remove with a high-pressure cleaner.

УСЛОВИЯ ЗА НАНАСЯНЕ
Minimum ambient temperature : 10 ºC
Maximum relative humidity : 80%
Minimum surface temperature : 8 ºC
Maximum surface temperature : 25 ºC

ПОЧИСТВАНЕ НА ОБОРУДВАНЕ И РАЗЛИВИ
Rinse with clean water immediately after use.

ЗАБЕЛЕЖКИ
Dispose of remnants of the product and empty packaging as chemical waste in accordance with the local regulations and legal requirements.

СРОК НА ГОДНОСТ
Can be kept for a minimum of 12 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

Дата на издаване: 29/05/2026

Налични цветове и размери на опаковките: Моля, вижте съответната продуктова страница на www.rust-oleum.eu, за да се запознаете с актуалните налични цветове и размери на опаковките.

Отказ от отговорност: Информацията, съдържаща се в този документ, доколкото ни е известно, е вярна и точна и се предоставя добросъвестно, но без гаранция. Счита се, че потребителят се е уверил самостоятелно в пригодността на нашите продукти за неговата/нейната конкретна цел. При никакви обстоятелства Rust-Oleum Europe не носи отговорност за последващи или случайни щети. Продуктите трябва да се съхраняват, обработват и нанасят при условия, съответстващи на препоръките на Rust-Oleum Europe, подробно описани в последното копие на информационния лист на продукта. Отговорност на потребителите е да се уверят, че разполагат с актуалното копие. Последните копия на информационния лист за продукта са на разположение безплатно и могат да бъдат изтеглени от www.rust-oleum.eu или при запитване до нашия отдел за обслужване на клиенти. Rust-Oleum Europe си запазва правото да променя свойствата на своите продукти без предварително уведомление.

Rust-Oleum Netherlands B.V.
Europalaan 9
5232 BC 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu