



B-WAX

Sacrificial anti-graffiti coating

- Suitable for a wide variety of surfaces, porous, or smooth
- Virtually invisible
- Weather resistant
- Does not damage the environment
- Water permeable

B-WAX

POPIS PRODUKTU (DLHÝ)

It is a virtually invisible, environmentally-friendly, anti-graffiti and anti-poster coating based on natural waxes for all surfaces resistant to water from minimally 60 °C.

ODPORÚČANÉ POUŽITIE

This is a sacrificial anti-graffiti coating for all mineral construction materials, natural stone, and other façade cladding.

TECHNICAL DATA

Hustota (g/cm³): 1,02 kg/l
Úroveň lesku: Satin

DRY_TIMES_BY_20

Na dotyk suché: N/A
Suchý na opäťovné natieranie: N/A
Úplne vytvrdenuté: N/A

TEORETICKÁ SPOTREBA

3 – 5 m² / l in a 2 layer system.

NÁVOD NA POUŽITIE

Clean the surface with an appropriate Prochemko façade cleaning agent and allow the surface to dry.

Remove previously applied graffiti remover using Topper or Removex Green.

Spray off with water under high pressure.

Apply B-Wax on a dry surface using a brush, roller, or low-pressure hand spray.

For optimal results with a standard system, apply a second layer crosswise after a two-hour drying time.

Remove graffiti using high-pressure hot water minimally at 80 °C. Then apply the new system.

First apply Prochemko Grease Cleaner Foam to old layers of B-Wax. Then allow it to soak in for a few minutes. Now wipe all of it with a hard brush and remove with a high-pressure cleaner.

PODMIENKY APLIKÁCIE

Minimum ambient temperature : 10 °C
Maximum relative humidity : 80%
Minimum surface temperature : 8 °C
Maximum surface temperature : 25 °C

ČISTENIE ZARIADENIA / POSTRIEKANIE

Rinse with clean water immediately after use.

POZNÁMKY

Dispose of remnants of the product and empty packaging as chemical waste in accordance with the local regulations and legal requirements.

SKLADOVATEĽNOSŤ

Can be kept for a minimum of 12 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

last_updated: 05/02/2025

footer_data_colors_pack_sizes: footer_data_colors_pack_sizes.value

footer_data_disclaimer: footer_data_disclaimer.value

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zellem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu