



EASY-WAX R

Cleaning and protective agent in one

- Colour and gloss restorative
- Very easy to apply
- Reduces adhesion of dirt
- Glossy layer
- For plastic, frames/panels, dam wall profiles, and coated surfaces

EASY-WAX R

DESCRIPTION

A cleaning and preservative in one based on polymers and protective waxes for plastic, frames/panels, sheet piling profiles, and coated surfaces.

RECOMMENDED USE

Cleaning and protective agent for plastic window sashes, coated aluminium, trapezoidal sheets, and painted surfaces.

Particularly effective on paint streaks and weathering.

THEORETICAL CONSUMPTION

18 – 25 m²/l

DIRECTIONS FOR USE

Apply a full layer of Easy-Wax R on a dry surface using a sponge or cloth. Wipe heavily soiled surfaces with a white non-woven nylon pad until the dirt is dissolved.

After drying for at least 15 minutes, mechanically or manually rub the surface until you achieve a smooth glossy layer.

APPLICATION CONDITIONS

Minimum ambient temperature : 5 °C

Maximum relative humidity : 100%

Minimum surface temperature : 5 °C

Maximum surface temperature: 35 °C

CLEANING OF EQUIPMENT / SPILLS

Rinse with clean water immediately after use.

REMARKS

Remnants of this product should be treated as chemical waste and may not be disposed of together with business maintenance waste.

PH

7.0000

SHELF LIFE

Can be kept for a minimum of 12 months after the date of delivery when stored in a dry, cool, and frost-free environment in the unopened original packaging.

Date issued: 05/07/2022

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu