



GEVEX

Extremely concentrated façade cleaner

- Very quick and effective cleaner
- Cleans heavy grime
- Suitable for surfaces not sensitive to acids
- Dilute with water maximally to a ratio of 1: 5

GEVEX

DESCRIPTION

A powerful façade cleaner based on hydrogen fluoride (HF) for removing heavy grime from façades, terraces, partitions, garden walls, etc.

RECOMMENDED USE

Gevex is suitable for cleaning all mineral construction materials, such as façade, terraces, partitions, garden walls, etc.

Do not use on limestone-based and carbonate-based surfaces.

Always try out a test surface.

THEORETICAL CONSUMPTION

4 - 6 m²/l

PRACTICAL CONSUMPTION

Consumption is greatly dependent on the amount of dirt, dilution, and type of surface.

DIRECTIONS FOR USE

- Dilute as needed maximally to a ratio of 1 : 5 with water.
- Apply Gevex using a brush.
- Systematically work from the bottom to the top.
- Allow the product to soak in for 30 seconds to half an hour.
- First, rinse off with a lot of water, then with water under a suitable pressure supplied at 16 to 20 litres per minute.

APPLICATION CONDITIONS

Minimum ambient temperature : 5 °C

Maximum relative humidity : 100%

Minimum surface temperature : 5 °C

Maximum surface temperature: 30 °C

CLEANING OF EQUIPMENT / SPILLS

Rinse with clean water immediately after use.

REMARKS

Harmful to all lime-based and metal-oxide based types of stone, glass, polished marble, glazed tiles, paintwork, and varnishing, etc.

Dispose of the product and empty packaging as chemical waste in accordance with the local regulations and legal requirements.

pH value when diluted with water to a ratio of 1:5: approx. 2.5.

Hazard

- Fatal when swallowed and in contact with the skin
- Poisonous when inhaled.
- Causes serious burns and eye injuries

Prevention

- Thoroughly wash your hands after working with this product.
- Only use outdoors or in a well-ventilated space.
- Do not eat, drink, or smoke when using this product.
- Wear protective gloves and face protection.
- Wear an apron or overalls when there is a chance of spatters.
- Wear goggles, face protection, or other full-face protection when there is a chance of direct exposure to aerosols or spatters.

Reaction

AFTER INHALING:

- Bring the person out into fresh air and ensure that can breathe easily.
- Immediately consult a doctor.

AFTER SWALLOWING:

- Rinse the mouth.
- Do not induce vomiting.

CONTACT WITH THE SKIN (or hair):

- Immediately remove contaminated clothing.
- Rinse off the skin with water or take a shower.

CONTACT WITH THE EYES:

- Carefully rinse with water for several minutes.
- If possible, remove contact lenses.
- Continue to rinse.

Storage

- In a well-ventilated location.
- Store in properly closed packaging.
- Keep locked up.
- Dispose of the content and container in accordance with local, regional, national, and international regulations.

PH

0.0000

SHELF LIFE

Can be kept for a minimum of 12 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

Date issued: 13/09/2022

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu