



## CHALK-CEMENT-EX CONCENTRATE

# Effortlessly removes lime and cement deposits

- Effective action and result
- For acid-resistant surfaces
- Wide range of use
- Can be rinsed off with water

# CHALK-CEMENT-EX CONCENTRATE

## DESCRIPTION

For the easy removal of old and hard lime and cement deposits from acid-proof surfaces. Also suitable for the removal of cement scum.

## RECOMMENDED USE

Chalk-Cement-Ex Concentrate is suitable for removing lime and cement residues from a variety of acid-resistant surfaces. It is also suitable for use as an 'etching agent' for smooth cement-based floors, and so on, and as a descaler for pipes, boilers, etc.

## PRACTICAL CONSUMPTION

Maximum dilution: 1:10. Consumption is heavily dependent on the level of dirt and the desired result.

## DIRECTIONS FOR USE

Dilute Chalk-Cement-Ex Concentrate with water to maximally 1:10. In case of vertical surfaces, work from the bottom to the top to avoid runs and streaks. Apply the product using a sponge or hand spray gun and allow to soak in for 5 to 10 minutes. If necessary, use a car-washing brush or white pad as an aid. If the red colour changes into a yellowish white colour before the desired end result is achieved, Chalk-Cement-Ex must be reapplied. After use, rinse thoroughly with water until a neutral surface is obtained. Chalk-Cement-Ex Concentrate applications, such as in refill spray bottle, dilute in the mixture ratio of 150 ml Chalk-Cement-Ex Concentrate to 350 ml clean water. First, try out a test surface.

## APPLICATION CONDITIONS

Minimum ambient temperature: 5 °C  
Maximum relative humidity: 100%  
Minimum surface temperature: 5 °C  
Maximum surface temperature: 35 °C

## CLEANING OF EQUIPMENT / SPILLS

Rinse with clean water immediately after use.

## REMARKS

Dispose of remnants of the product and empty packaging as chemical waste, in accordance with the local regulations and legal requirements.

## PH

1

## SHELF LIFE

Can be kept for a minimum of 12 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

Date issued: 05/02/2025

**Available colours & pack sizes:** Please refer to the respective product page on [www.rust-oleum.eu](http://www.rust-oleum.eu) for an overview of actual available colours and pack sizes.

**Disclaimer:** The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from [www.rust-oleum.eu](http://www.rust-oleum.eu) or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T : +31 (0) 165 593 636  
F : +31 (0) 165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T : +44 (0)1914 113 146  
F : +44 (0)1914 113 147  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T : +33(0) 130 40 00 44  
F : +33(0) 130 40 99 80  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T : +32 (0) 13 460 200  
F : +32 (0) 13 460 201  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)