



PROCHEMKO



KURALTEX NL 320

Neutral cleaner for all types of surfaces

- Effective removal of atmospheric dirt
- Concentrated formula, can be diluted to a max. of 1 : 20
- Ideal for regular maintenance of coated surfaces
- Biodegradable
- Suitable for window frames, plastic, floors etc.

KURALTEX NL 320

DESCRIPTION

Concentrated neutral cleaner based on surfactants, ideal for the regular maintenance of coated surfaces.

RECOMMENDED USE

Kuraltex NL 320 is suitable for cleaning coated surfaces, plastic surfaces and anodised aluminium before finishing them with Kuraltex LP 312, Kuraltex RB 313 or Kuraltex BL 314.

RECOMMENDED SYSTEM

Pre-treatment : Kuraltex N320
First layer : Kuraltex LP 312

Pre-treatment : Kuraltex NL 320
First layer : Kuraltex RB 313

Pre-treatment : Kuraltex NL 320
First layer : Kuraltex BL 314 or KuraltexPrimer
Second layer : Kuraltex BL 314

THEORETICAL CONSUMPTION

Approx 10 m²/l.

PRACTICAL CONSUMPTION

Consumption depends heavily on the amount of dirt.

DIRECTIONS FOR USE

- Cleaning: Dilute Kuraltex NL 320 to a maximum of 1:5, depending on the level of pollution
- Periodic washing: Dilute Kuraltex NL 320 with water to a maximum of 1:20
- Apply the product using a sponge, misting nozzle or manual low pressure nozzle and allow to work for a few minutes
- Do not allow the product to dry out
- Rinse or spray off with clean water
- A car washing brush or white pad may be used to help

APPLICATION CONDITIONS

Minimum ambient temperature: 5°C
Maximum relative humidity : 100%
Minimum surface temperature : 5°C.
Maximum surface temperature: 30°C.

CLEANING OF EQUIPMENT / SPILLS

Rinse with clean water directly after use.

REMARKS

Dispose of remaining product and empty packaging as chemical waste, in accordance with the local regulations and legal requirements.

PH

7,50

SHELF LIFE

Minimum of 12 months when stored in a dry, cool and frost-free environment in the original, unopened packaging.

Date issued: 05/02/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu