



KURALTEX PRIMER

Primer for pre-treatment of Kuraltex BL 314

- Prevents sinking and improves the adhesion of Kuraltex BL 314
- Prevents migration of plasticisers and film-forming admixtures
- Closes off pores
- Invisible
- For frames, plastics, and coated surfaces

KURALTEX PRIMER

DESCRIPTION

A water-based primer based on acrylic and polyurethane dispersion for anodised aluminium, coated metal surfaces, and a variety of plastics.

RECOMMENDED USE

For use as an invisible primer on chalky coatings.
Waterproofs and improves the adhesion on anodised aluminium.

TECHNICAL DATA

Density (g/cm³): 1,02 kg/l
Solids content in volume: 17%

DRY TIMES BY 20° C/RH 50%

Touch dry: N/A
Dry to recoat: N/A
Fully cured: N/A

PRACTICAL CONSUMPTION

The actual consumption is dependent on the absorptive capacity of the surface.

DIRECTIONS FOR USE

- Use Kuraltext Primer as supplied.
- Apply the product using a velvet roller.
- Allow the product to dry for at least an hour at 20 °C before that you apply Kuraltext BL 314.

APPLICATION CONDITIONS

Minimum ambient temperature : 5 °C
Maximum relative humidity : 100%
Minimum surface temperature : 5 °C
Maximum surface temperature: 35 °C

CLEANING OF EQUIPMENT / SPILLS

Rinse with clean water immediately after use.

PH

8.0000

SHELF LIFE

Can be kept for a minimum of 12 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

Date issued: 17/10/2022

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu