



## KURALTEX PRIMER

# Primer for pre-treatment of Kuraltex BL 314

- Prevents sinking and improves the adhesion of Kuraltex BL 314
- Prevents migration of plasticisers and film-forming admixtures
- Closes off pores
- Invisible
- For frames, plastics, and coated surfaces

# KURALTEX PRIMER

## DESCRIPTION

A water-based primer based on acrylic and polyurethane dispersion for anodised aluminium, coated metal surfaces, and a variety of plastics.

## RECOMMENDED USE

For use as an invisible primer on chalky coatings.  
Waterproofs and improves the adhesion on anodised aluminium.

## TECHNICAL DATA

Density (g/cm<sup>3</sup>): 1,02 kg/l  
Solids content in volume: 17%

## DRY TIMES BY 20° C/RH 50%

Touch dry: N/A  
Dry to recoat: N/A  
Fully cured: N/A

## PRACTICAL CONSUMPTION

The actual consumption is dependent on the absorptive capacity of the surface.

## DIRECTIONS FOR USE

- Use Kuraltext Primer as supplied.
- Apply the product using a velvet roller.
- Allow the product to dry for at least an hour at 20 °C before that you apply Kuraltex BL 314.

## APPLICATION CONDITIONS

Minimum ambient temperature : 5 °C  
Maximum relative humidity : 100%  
Minimum surface temperature : 5 °C  
Maximum surface temperature: 35 °C

## CLEANING OF EQUIPMENT / SPILLS

Rinse with clean water immediately after use.

## PH

8

## SHELF LIFE

Can be kept for a minimum of 12 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

Date issued: 05/02/2025

**Available colours & pack sizes:** Please refer to the respective product page on [www.rust-oleum.eu](http://www.rust-oleum.eu) for an overview of actual available colours and pack sizes.

**Disclaimer:** The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from [www.rust-oleum.eu](http://www.rust-oleum.eu) or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T : +31 (0) 165 593 636  
F : +31 (0) 165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T : +44 (0)1914 113 146  
F : +44 (0)1914 113 147  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T : +33(0) 130 40 00 44  
F : +33(0) 130 40 99 80  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T : +32 (0) 13 460 200  
F : +32 (0) 13 460 201  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)