



## MURODEX BIO

# Environmentally friendly, effective façade cleaner

- Powerful dirt dissolver without acids or solvents
- Environment and user-friendly
- Also works at lower temperatures
- For concrete, masonry, washable gravel grids, and mineral decorative plasters
- Economical to use

# MURODEX BIO

## DESCRIPTION

A water-based façade cleaner based on special bacteria and enzyme cultures for environmentally friendly and acid-free and alkaline-free cleaning of mineral construction materials.

## RECOMMENDED USE

Murodex Bio is a special cleaner for mineral construction materials, such as building brick, concrete, natural stone, washed gravel plates, and cement-based stucco layers, and is very suitable for cleaning mineral stucco layers in façade insulation systems.

## DIRECTIONS FOR USE

Dilute Murodex Bio with water maximally to a ratio of 1:3 depending on the degree of fouling.

Apply and saturate with Murodex Bio using the plastic pressurised sprayer, a square brush, or hand brush.

Wipe the chosen surface with a hard brush.

Allow all of it to soak in for at least 48 hours.

After the soak in period, spray off with a high-pressure cleaner.

Before use, we recommend trying out a test surface to help determine consumption and efficacy on a specific surface and determine fouling.

## APPLICATION CONDITIONS

Minimum ambient temperature : 10 °C

Maximum relative humidity : 100%

Minimum surface temperature : 10 °C

Maximum surface temperature: 35 °C

## CLEANING OF EQUIPMENT / SPILLS

Rinse with clean water immediately after use.

## REMARKS

Dispose of remnants of the product and empty packaging as chemical waste in accordance with the local regulations and legal requirements.

## PH

7

## SHELF LIFE

Can be kept for a minimum of 12 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

Date issued: 05/02/2025

**Available colours & pack sizes:** Please refer to the respective product page on [www.rust-oleum.eu](http://www.rust-oleum.eu) for an overview of actual available colours and pack sizes.

**Disclaimer:** The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from [www.rust-oleum.eu](http://www.rust-oleum.eu) or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T : +31 (0) 165 593 636  
F : +31 (0) 165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T : +44 (0)1914 113 146  
F : +44 (0)1914 113 147  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T : +33(0) 130 40 00 44  
F : +33(0) 130 40 99 80  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T : +32 (0) 13 460 200  
F : +32 (0) 13 460 201  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)