

PROCHEMKO



MURODEX HC

Removes heavy grime

- Removes heavy grime effectively
- Removes soot and atmospheric deposits
- Concentrated formula, dilute maximally to a ratio of 1: 20
- Solvent free
- For natural and artificial stone, plaster, and (wall) paint layers

MURODEX HC

DESCRIPTION

An alkaline cleaning agent that removes black deposits, such as soot, atmospheric dirt, and so on, in both dry and humid spaces, e.g. kitchens, cellars, bathrooms, swimming pools, and near fireplaces.

RECOMMENDED USE

Murodex HC can be used on all natural and plastic stone, plasterwork, and (wall) paint layers. Murodex HC can be specially used for kitchen, cellar, and outdoors walls. Always try out a test surface because of the strong bleaching/colour-removing action.

PRACTICAL CONSUMPTION

Consumption is heavily dependent on the contamination and the roughness of the surface.

DIRECTIONS FOR USE

Dilute Murodex HC with water, depending on the degree of contamination, maximally to a ratio of 1:20.

Apply the product using a brush or hand brush and allow to soak in for at least 5 minutes until the results can be seen.

If necessary, use a brush or white pad as an aid.

Rinse thoroughly with water until a neutral surface is obtained.

First, try out a test surface.

Do not use in combination with other cleaning products.

APPLICATION CONDITIONS

Minimum ambient temperature : 5 °C

Maximum relative humidity : 100%

Minimum surface temperature : 5 °C

Maximum surface temperature: 35 °C

CLEANING OF EQUIPMENT / SPILLS

Rinse with clean water immediately after use.

REMARKS

Dispose of remnants of the product and empty packaging as chemical waste in accordance with the local regulations and legal requirements.

PH

10.5000

SHELF LIFE

Can be kept for a minimum of 12 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

Date issued: 06/09/2022

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu