



NANOSIGN® COATEX PROTECTOR

Transparent protection agent (UV and Graffiti)

- Not yellowing
- High durability
- Fast drying (cured after 24 hours)
- Very good anti graffiti properties
- Economical in price

NANOSIGN® COATEX PROTECTOR

DESCRIPTION

A one-component transparent protective agent (UV and graffiti) based on nanotechnology (titanium oxide) polysilazanes.

Specially developed for long-term protection of closed surfaces.

RECOMMENDED USE

NanoSign-Coatex Protector is a protective coating system for the most common closed surfaces such as plastic, paint systems, metals, non-ferrous metals, plastic and metal foil, etc.

Excellently effective as an anti-graffiti coating on all above mentioned surfaces.

RECOMMENDED SYSTEM

recommended system

TECHNICAL DATA

Density (g/cm³): 0,82
Gloss Level: Gloss

DRY TIMES BY 20° C/RH 50%

Touch dry: 2 hours
Dry to handle: 2 hours
Dry to recoat: 12 - 16 hours
Fully cured: 20 - 24 hours

RECOMMENDED DRY FILM THICKNESS

2 µm

THEORETICAL CONSUMPTION

With a dry layer thickness of 2.5 micrometers: 25 -50 m²/liter

PRACTICAL CONSUMPTION

The practical consumption is highly dependent on the substrate and application method.

DIRECTIONS FOR USE

Apply NanoSign-Coatex Protector on a dry, clean and dirt / grease-free surface in one layer. Apply the product using a lint-free cloth, by spraying, a short-haired roller or mohair application pad. Apply in a very thin layer.

CLEANING OF EQUIPMENT / SPILLS

Immediately after use with Graftex 4

SHELF LIFE

Minimum of 6 months from the delivery date, provided between + 0 ° C and 30 ° C in unopened original packaging.

Date issued: 05/02/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu