



## **NANOSIGN® COATEX PROTECTOR**

### **Transparent protection agent (UV and Graffiti)**

- Not yellowing
- High durability
- Fast drying (cured after 24 hours)
- Very good anti graffiti properties
- Economical in price

# NANOSIGN® COATEX PROTECTOR

## DESCRIPTION

A one-component transparent protective agent (UV and graffiti) based on nanotechnology (titanium oxide) polysilazanes.

Specially developed for long-term protection of closed surfaces.

## RECOMMENDED USE

NanoSign-Coatex Protector is a protective coating system for the most common closed surfaces such as plastic, paint systems, metals, non-ferrous metals, plastic and metal foil, etc.

Excellently effective as an anti-graffiti coating on all above mentioned surfaces.

## RECOMMENDED SYSTEM

recommended system

## TECHNICAL DATA

Density (g/cm<sup>3</sup>): 0,82  
Gloss Level: Gloss

## DRY TIMES BY 20° C/RH 50%

Touch dry: 2 hours  
Dry to handle: 2 hours  
Dry to recoat: 12 - 16 hours  
Fully cured: 20 - 24 hours

## RECOMMENDED DRY FILM THICKNESS

2 µm

## THEORETICAL CONSUMPTION

With a dry layer thickness of 2.5 micrometers: 25 -50 m<sup>2</sup>/liter

## PRACTICAL CONSUMPTION

The practical consumption is highly dependent on the substrate and application method.

## DIRECTIONS FOR USE

Apply NanoSign-Coatex Protector on a dry, clean and dirt / grease-free surface in one layer. Apply the product using a lint-free cloth, by spraying, a short-haired roller or mohair application pad. Apply in a very thin layer.

## CLEANING OF EQUIPMENT / SPILLS

Immediately after use with Grafitex 4

## SHELF LIFE

Minimum of 6 months from the delivery date, provided between + 0 ° C and 30 ° C in unopened original packaging.

Date issued: 05/02/2025

**Available colours & pack sizes:** Please refer to the respective product page on [www.rust-oleum.eu](http://www.rust-oleum.eu) for an overview of actual available colours and pack sizes.

**Disclaimer:** The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from [www.rust-oleum.eu](http://www.rust-oleum.eu) or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T : +31 (0) 165 593 636  
F : +31 (0) 165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T : +44 (0)1914 113 146  
F : +44 (0)1914 113 147  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T : +33(0) 130 40 00 44  
F : +33(0) 130 40 99 80  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T : +32 (0) 13 460 200  
F : +32 (0) 13 460 201  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)