



## NANOSIGN® COATEX STRUCTURE

### 2K coating to prevent posters being posted on surfaces

- Permanent
- one-layer system, easy to apply
- Simple to clean
- Does not contain granules
- Available in most RAL colours

# NANOSIGN® COATEX STRUCTURE

## DESCRIPTION

A two-component coating based on polyurethane in combination with nanotechnology (silanes with UV additives).  
Particularly suitable as a treatment to preventing the posting of posters or stickers for a variety of non-porous surfaces.  
Available in a variety of colours.

## RECOMMENDED USE

NanoSign Coatex Structure is a durable protection system that is an anti-poster (sticker) treatment on non-porous surfaces, such as metal, plastic, and a variety of paint systems.  
To obtain the optimal result, finish the texture layer with NanoSign Non-Stick Coating.

## PRACTICAL CONSUMPTION

The consumption can vary a great deal depending on the layer thickness and the associated roughness of the structure.

## DIRECTIONS FOR USE

Apply NanoSign Coatex Structure to a dry, clean, grease-free, and dirt-free surface in a single layer.  
Apply the product using a fleece roller, then use a yellow gel or fleece roller to achieve the desired anti-poster structure.  
The layer thickness applied determines the coarseness of the texture.

## APPLICATION CONDITIONS

Minimum ambient temperature : 5 °C  
Maximum relative humidity : 100%  
Minimum surface temperature : 5 °C  
Maximum surface temperature: 35 °C

## CLEANING OF EQUIPMENT / SPILLS

Grafitex 4 of thinner

## REMARKS

Remnants of this product and not completely cleaned packaging should be treated as chemical waste and may not be disposed of together with business maintenance waste, other than in accordance with the Environmental Management Act.

## SHELF LIFE

Can be kept for a minimum of 6 months when stored in a dry, cool and frost-free environment in the original unopened packaging.

Date issued: 05/02/2025

**Available colours & pack sizes:** Please refer to the respective product page on [www.rust-oleum.eu](http://www.rust-oleum.eu) for an overview of actual available colours and pack sizes.

**Disclaimer:** The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from [www.rust-oleum.eu](http://www.rust-oleum.eu) or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T : +31 (0) 165 593 636  
F : +31 (0) 165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T : +44 (0)1914 113 146  
F : +44 (0)1914 113 147  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T : +33(0) 130 40 00 44  
F : +33(0) 130 40 99 80  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T : +32 (0) 13 460 200  
F : +32 (0) 13 460 201  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)