



NANOSIGN® EASYWAX

A high-quality cleaner and protective agent

- Does not yellow
- High durability
- Water and weather resistant
- Economical in price
- Very easily applied

NANOSIGN® EASYWAX

DESCRIPTION

A high-quality cleaner and protective agent based on nanotechnology for treating non-porous surfaces. Provides longer protection than conventional wax products.

RECOMMENDED USE

NanoSign-EasyWax is suitable for temporarily protecting coated surfaces, plastic surfaces, and both non-ferrous and ferrous metals, such as stainless steel.

DRY TIMES BY 20° C/RH 50%

Touch dry:	10 minutes
Dry to recoat:	N/A
Fully cured:	4-6 hours

DIRECTIONS FOR USE

- Dissolve dirt with water.
- Remove stubborn dirt with Kuraltex NL 320 or VB 311.
- Shake well before use.
- Rub in NanoSign-EasyWax using a cloth or sponge.
- Apply the product evenly and very thinly.
- Very suitable for use in an eccentric polishing machine.
- After a few minutes drying time, wipe with a clean cloth (the protection layer will be completely cured after a few hours).
- For large areas, make a test piece to determine the evenness of the result.

APPLICATION CONDITIONS

Minimum ambient temperature : 5 °C
Maximum relative humidity : 100%
Minimum surface temperature: 5 °C
Maximum surface temperature: 35 °C

CLEANING OF EQUIPMENT / SPILLS

Rinse with water immediately after use.

PH

8.0000

SHELF LIFE

Can be kept for a minimum of 12 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

Date issued: 14/09/2022

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu