



## **NANOSIGN® EASYWAX POLISH**

### **High-quality polish & protective agent**

- Original colour restored
- Polishing and Waxing in one go
- Easy to apply
- Economical solution
- Water and weather resistant

# NANOSIGN® EASYWAX POLISH

## DESCRIPTION

High-quality polish & protective agent. Especially developed for coated surfaces (mono-colours) with ultra-violet damage (weathering).

## RECOMMENDED USE

This is a polishing agent and temporary protection for coated surfaces (mono colours). It is not suitable for profiled surfaces, metallic coatings, or patina layers.

## DIRECTIONS FOR USE

### CLEAN UP:

Clean the weathered surface with Prochemko Grease Cleaner Foam (1 to 4) using a high-pressure foam pump.

If needed, you can use a white nylon pad as an aid when cleaning up light weathering or wet sand using WP sandpaper 2000 to clean up heavy weathering.

Afterwards, thoroughly wash the surface with water

### POLISHES AND WAXES:

Thoroughly shake NanoSign Easy-Wax Polish before use.

Apply with a stiff microfibre or hard-foam pad and polish the surface using an eccentric polisher, such as the Rupes LHR Bigfoot 75E mini (or equivalent) or Bigfoot LHR 21ES/HG (or equivalent).

Note:

1. Apply thinly and evenly
2. Start out at a low RPM and gradually increase the RPMs to achieve the desired effect.
3. Make sure the polishing pad is flush with the surface to prevent excessive heat development.

After polishing and drying using a microfibre cloth, rub until an evenly glossy surface is achieved.

For large areas, test a piece to assess the evenness of the result

## APPLICATION CONDITIONS

Minimum ambient temperature : 5 °C

Maximum relative humidity : 100%

Minimum surface temperature: 5 °C

Maximum surface temperature: 35 °C

## CLEANING OF EQUIPMENT / SPILLS

Rinse with water immediately after use.

## REMARKS

Product remnants and the empty containers must be disposed of as chemical waste in compliance with local regulations and laws.

## PH

8

## SHELF LIFE

Can be kept for a minimum of 12 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

Date issued: 05/02/2025

**Available colours & pack sizes:** Please refer to the respective product page on [www.rust-oleum.eu](http://www.rust-oleum.eu) for an overview of actual available colours and pack sizes.

**Disclaimer:** The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from [www.rust-oleum.eu](http://www.rust-oleum.eu) or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T : +31 (0) 165 593 636  
F : +31 (0) 165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T : +44 (0)1914 113 146  
F : +44 (0)1914 113 147  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T : +33(0) 130 40 00 44  
F : +33(0) 130 40 99 80  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T : +32 (0) 13 460 200  
F : +32 (0) 13 460 201  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)