



## **NANOSIGN® GLASS**

# **1K Protective agent for coating glass**

- · Water and dirt repellent
- · 'Easy to Clean' surface
- · Highly durable
- · Easy to apply
- · One-component system

### **NANOSIGN® GLASS**

#### DESCRIPTION

A one-component protective agent for glass and many other types of smooth surfaces based on nanotechnology (silanes).

Its highly oleophobic and hydrophobic properties prevents water drops adhering to the surface and also make a surface really easy to clean.

#### **RECOMMENDED USE**

NanoSign Glass is a protective agent for mirrors, car windows, glass, and glazed surfaces in general. Also suitable for chromed metals, such as on cranes and similar.

#### **TECHNICAL DATA**

Density (g/cm³): 0,8 g/ml Solids content in volume: 9%

#### DRY TIMES BY 20° C/RH 50%

Touch dry: 10 minutes
Fully cured: 6 hours

#### THEORETICAL CONSUMPTION

40-80 m<sup>2</sup>/kg

#### PRACTICAL CONSUMPTION

The actual consumption is dependent on the method of application.

#### **DIRECTIONS FOR USE**

Soak a lint-free cotton cloth with NanoSign Glass and then apply the product on about  $0.5\ m^2$  of the surface to be treated.

Polish using a dry cloth until the surface is clear and 'blur-free'.

Repeat these steps for the rest of the surface.

To achieve a durable treatment, the treated surface must not come into contact with water or people's hands for two hours after the treatment.

#### **CLEANING OF EQUIPMENT / SPILLS**

Isopropyl alcohol

#### **REMARKS**

Remnants of this product should be treated as chemical waste and may not be disposed of together with business maintenance waste.

#### **SHELF LIFE**

Can be kept for a minimum of 6 months from the date of delivery when stored at between 0 °C and 30 °C in the unopened original packaging.

Date issued: 05/02/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V. Zilverenberg 16 5234 GM 's-Hertogenbosch The Netherlands T: +31 (0) 165 593 636

The Netherlands
T: +31 (0) 165 593 636
F: +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
Dh3 2RE United Kingdom
T: +44 (0)1914 113 146
F: +44 (0)1914 113 147
into@nist-leum eu

Rust-Oleum France S.A.S. 38, av. du Gros Chêne 95322 Herblay France T: +33(0) 130 40 00 44 F: +33(0) 130 40 99 80 N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T: +32 (0) 13 460 200
F: +32 (0) 13 460 201
info@rust-oleum.eu