

PROCHEMKO



...zij een kans!



OUT OF ASSORTMENT

NANOSIGN® SILANE PRIMER

Adhesive primer for anti-slip coatings

- Extreme adhesion improvement
- Can be applied to all smooth and non-porous surfaces containing silicate
- Quick drying
- Suitable for all types of paints and coatings
- Improves surface resistance to moisture

NANOSIGN® SILANE PRIMER

DESCRIPTION

A transparent adhesive primer specially for the anti-slip coatings and other one or two-component coatings for use on silicate-based natural stone (granite, gneiss, etc.), glass, and glazed tiles.

RECOMMENDED USE

NanoSign Silane Primer is a transparent adhesion promoter for one and two-component coatings for use on silicate-based natural stone (granite, gneiss, etc.), glass, and glazed tiles. Extremely suitable as a pre-treatment on smooth surfaces for NanoSign AntiSlip PU. Can be used both indoors and outdoors.

THEORETICAL CONSUMPTION

5-20 m²/l

PRACTICAL CONSUMPTION

The actual efficiency is dependent on the roughness of the surface and the application technique.

DIRECTIONS FOR USE

Apply NanoSign Silane Primer on a thoroughly cleaned surface
Clean the surface with Grease Cleaning Foam and rinse off well
Apply in one thin layer using a moist cloth
Once evaporated, apply the coating for 5 to 10 minutes

APPLICATION CONDITIONS

Minimum ambient temperature : 5 °C
Maximum relative humidity : 100%
Minimum surface temperature : 5 °C
Maximum surface temperature: 35 °C

REMARKS

Product remnants and the empty containers must be disposed of as chemical waste in compliance with local regulations and laws.

SHELF LIFE

Can be kept for a minimum of 12 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

Date issued: 19/04/2022

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu