



NANOSIGN® ULTRADRY SW

A water-based hydrophobic sealant based on nanotechnology.

- Water vapour permeable
- Virtually invisible
- Prevents salts and lime efflorescing
- Powerful water-repellent efflorescence
- Also usable on bare wood

NANOSIGN® ULTRADRY SW

DESCRIPTION

A water-based hydrophobic sealant based on siloxanes and nanotechnology that produces a strong water-repellent effect.

Suitable for mineral surfaces, such as masonry, concrete, sand-lime brick, mineral plasterwork, joint mortars, porous natural stone, and many types of untreated wood.

RECOMMENDED USE

This is a hydrophobic sealant for masonry, concrete, sand-lime brick, mineral mortars, and slightly porous natural stone, and a variety of untreated non-porous woods, such as deal and European pine.

THEORETICAL CONSUMPTION

4-5 m²/l

PRACTICAL CONSUMPTION

We recommend that before starting work you carry out a test to assess the rate of consumption.

DIRECTIONS FOR USE

The surfaces must be treated free of dust and grease.

NanoSign Ultra Dry SW does not fill gaps, so any pointing in poor condition should be repaired beforehand.

Before applying, protect surrounding materials, such as window sashes, windows, and plants.

Apply NanoSign Ultra Dry SW using a low-pressure spray gun, (atomiser) and rolling with a short fleece roller.

APPLICATION CONDITIONS

Minimum ambient temperature : 5 °C

Maximum relative humidity : 80%

Minimum surface temperature : 5 °C

Maximum surface temperature: 35 °C

CLEANING OF EQUIPMENT / SPILLS

Rinse with clean water immediately after use.

PH

7

SHELF LIFE

Can be kept for a minimum of 6 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

Date issued: 05/02/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu