



## PREVOSIL GB

# Impregnation cream for hydrophobic sealant



- Meticulous work possible without taping
- Penetrates deep into the pores of the surface
- Usable on fresh dry pointing
- Reduces efflorescence of salts and lime
- Ideal for masonry, concrete, sand-lime brick, mineral mortars, and slightly porous natural stone

# PREVOSIL GB

## DESCRIPTION

A pasty water-based hydrophobic sealant based on silanes/siloxanes for application using brush, roller, or airless to be able to work accurately without taping off areas.

## RECOMMENDED USE

Pasty hydrophobic sealant for use on masonry, concrete, sand-lime brick, mineral mortars, and slightly porous natural stone.

## TECHNICAL DATA

Density (g/cm<sup>3</sup>): 1,02 kg/l  
Solids Content in weight: 12%

## DRY TIMES BY 20° C/RH 50%

Touch dry: N/A  
Dry to recoat: yes  
Fully cured: N/A

## THEORETICAL CONSUMPTION

0,1 – 0,3 kg/m<sup>2</sup>

## PRACTICAL CONSUMPTION

We recommend that before starting work you carry out a test to assess the rate of consumption.

## SURFACE PREPARATION

The surfaces to be treated must be free of dust and grease.

Prevosil® Special GB does not fill gaps, so any joints in poor condition should be repaired beforehand.

If necessary, treat sanded surfaces beforehand.

Apply a full layer allowing for the porosity of the surface. Apply working from the bottom to the top.

Before applying, protect surrounding materials, such as window sashes, windows, and plants.

Apply Prevosil® Special GB using a roller or brush, or by airless spraying.

## APPLICATION CONDITIONS

Minimum ambient temperature : 10 °C

Maximum relative humidity : 100%

Minimum surface temperature : 10 °C

Maximum surface temperature: 25 °C

## CLEANING OF EQUIPMENT / SPILLS

Rinse with water immediately after use.

## REMARKS

Dispose of remaining product and empty packaging as chemical waste, in accordance with the local regulations and legal requirements.

## PH

7.0000

## SHELF LIFE

Can be kept for a minimum of 6 months in a cool, dry and frost-free environment in the original unopened packaging.

Date issued: 17/10/2022

**Available colours & pack sizes:** Please refer to the respective product page on [www.rust-oleum.eu](http://www.rust-oleum.eu) for an overview of actual available colours and pack sizes.

**Disclaimer:** The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from [www.rust-oleum.eu](http://www.rust-oleum.eu) or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T : +31 (0) 165 593 636  
F : +31 (0) 165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T : +44 (0)1914 113 146  
F : +44 (0)1914 113 147  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T : +33(0) 130 40 00 44  
F : +33(0) 130 40 99 80  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T : +32 (0) 13 460 200  
F : +32 (0) 13 460 201  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)