



## **PREVOSIL SPECIAAL RE**

# **Solvent-based impregnating and hydrophobic agent**

- Strongly hydrophobic
- Colourless and almost invisible once dry
- Low-scent
- Vapour permeable system prevents frost damage
- Ideal for brick, concrete, natural stone, aerated concrete and more

# PREVOSIL SPECIAAL RE

## DESCRIPTION

Hydrophobic treatment based on an oligomeric siloxane, dissolved in an aliphatic hydrocarbon for mineral, porous surfaces.

## RECOMMENDED USE

On all mineral construction materials such as concrete, natural stone, brick, mineral grouting and stone-like panels. Prevents or reduces white salt efflorescence, frost damage, limescale contamination and surface erosion.

## TECHNICAL DATA

Density (g/cm<sup>3</sup>): 0,8 kg/l  
Solids Content in weight: 4%

## DRY TIMES BY 20° C/RH 50%

Touch dry: N/A  
Dry to recoat: N/A  
Fully cured: N/A

## THEORETICAL CONSUMPTION

0.7 - 2 m<sup>2</sup>/l

## PRACTICAL CONSUMPTION

A test should be completed before carrying out the entire project.

## DIRECTIONS FOR USE

The surfaces to be treated need to be free of dust and grease. Damage to the surface needs to be repaired beforehand. Apply Prevosil Special RE in two layers wet in wet, taking into account of the surface's absorbency, working to saturate from bottom to top. Avoid using when in full sun and at high temperatures. When in use avoid smoking and proximity to an open fire. During application, protect material in the vicinity, such as window frames, windows and plants.

## APPLICATION CONDITIONS

Minimum ambient temperature: 5°C  
Maximum relative humidity: 80%  
Minimum surface temperature: 5°C  
Maximum surface temperature: 25°C

## CLEANING OF EQUIPMENT / SPILLS

Rinse with water directly after use.

## REMARKS

Dispose of remaining product and empty packaging as chemical waste, in accordance with the local regulations and legal requirements.

## SHELF LIFE

Can be stored for a minimum of 6 months in a cool, dry and frost-free environment in the original, unopened packaging.

Date issued: 21/06/2022

**Available colours & pack sizes:** Please refer to the respective product page on [www.rust-oleum.eu](http://www.rust-oleum.eu) for an overview of actual available colours and pack sizes.

**Disclaimer:** The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from [www.rust-oleum.eu](http://www.rust-oleum.eu) or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T : +31 (0) 165 593 636  
F : +31 (0) 165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T : +44 (0)1914 113 146  
F : +44 (0)1914 113 147  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T : +33(0) 130 40 00 44  
F : +33(0) 130 40 99 80  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T : +32 (0) 13 460 200  
F : +32 (0) 13 460 201  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)