

PROCHEMKO



PREVOSIL SPECIAAL WB

Makes mineral surfaces such as facades water repellent

- Very high percentage of active components
- Penetrates deep into the surface
- Vapour permeable system prevents frost damage
- Alkali resistant
- Ideal for brick, concrete, natural stone, aerated concrete and more

PREVOSIL SPECIAAL WB

DESCRIPTION

Hydrophobic treatment with high levels of active components based on a water dispersion of silanes/siloxanes for mineral, porous surfaces.

RECOMMENDED USE

As a hydrophobic treatment for masonry, concrete, calcium silicate, mineral grouting and lightly porous natural stone.

TECHNICAL DATA

Density (g/cm³): 1,0 kg/l
Solids Content in weight: 7%

DRY TIMES BY 20° C/RH 50%

Touch dry: N/A
Dry to recoat: N/A
Fully cured: N/A

THEORETICAL CONSUMPTION

0.7 - 2 m²/l

PRACTICAL CONSUMPTION

We advise carrying out test before commencing activity in order to assess the right consumption level.

DIRECTIONS FOR USE

The surfaces to be treated need to be free of dust and grease. Prevosil Special WB does not fill gaps; any pointing in poor condition should be repaired beforehand. Any silted surfaces should first be treated with Prevosil CE. Application in two layers wet in wet, taking account of the surface's absorbency, and apply from bottom to top. During application, protect material in the vicinity, such as window frames, windows and plants. Apply Prevosil Special WB using the flow-coat system. (low pressure avoiding mist formation)

APPLICATION CONDITIONS

Minimum ambient temperature: 5°C
Maximum relative humidity: 100%
Minimum surface temperature: 5°C
Maximum surface temperature: 35°C

CLEANING OF EQUIPMENT / SPILLS

Rinse with water directly after use.

REMARKS

Certification report HD 340/133-14 from the Scientific and Technical Centrum for the construction industry in Brussels. Certification report R/25811/88 from the KU Leuven, Laboratorium Reyntjes in Leuven. Available on request.
Dispose of remaining product and empty packaging as chemical waste, in accordance with the local regulations and legal requirements.

PH

7

SHELF LIFE

Can be stored for a minimum of 12 months in a cool, dry and frost-free environment in the original, unopened packaging.

Date issued: 05/02/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu