



## **R.A.P.P. WB**

# **Paint and Coating stripper also for indoor use**

- Powerful paint stripper
- Water based
- For almost all surfaces
- Methylene chloride free

# R.A.P.P. WB

## DESCRIPTION

For the quick and efficient removal of just about all paint types.  
Also removes bitumen, adhesives, old wax layers, aerosol paints, and graffiti.  
For use on just about all surfaces.  
R.A.P.P. WB is water-based and suitable for indoor use.

## RECOMMENDED USE

R.A.P.P. WB is suitable for removing Alkyd paint, water-based paints, two-component epoxyethane and polyurethane coatings, and one-component polyurethane coatings. For use on almost all surfaces.  
Not for use on non-ferrous metal surfaces.  
With plastic and polyester, always try out a test surface.

## THEORETICAL CONSUMPTION

1 - 3 m<sup>2</sup>/kg

## PRACTICAL CONSUMPTION

Consumption is highly dependent on the layer thickness of the paint coating and the roughness of the surface.

## DIRECTIONS FOR USE

Apply a generous layer of the product on the surface to be treated.  
Let the product soak in for at least 30 minutes.  
Remove the paint remnants using a scraper, spatula, or, in the event of graffiti, a white pad.  
If necessary, repeat the treatment.  
When removing multiple paint layers, cover the R.A.P.P. Cover WB with plastic foil and allow to soak in for a few hours.  
Brush or spray off with (hot) water at an appropriately high pressure.  
After removing the old paint, clean the treated surface using Rodex diluted with water (1:10).

## APPLICATION CONDITIONS

Minimum ambient temperature : 5 °C  
Maximum relative humidity : 100%  
Minimum surface temperature : 5 °C  
Maximum surface temperature: 35 °C  
Low temperatures can slow down the working of the stripper.

## CLEANING OF EQUIPMENT / SPILLS

Rinse with water immediately after use, but with thinner if dried out.

## REMARKS

Dispose of remnants of the product and empty packaging as chemical waste in accordance with the local regulations and legal requirements.

## PH

3

## SHELF LIFE

Can be kept for a minimum of 12 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

Date issued: 05/02/2025

**Available colours & pack sizes:** Please refer to the respective product page on [www.rust-oleum.eu](http://www.rust-oleum.eu) for an overview of actual available colours and pack sizes.

**Disclaimer:** The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from [www.rust-oleum.eu](http://www.rust-oleum.eu) or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T : +31 (0) 165 593 636  
F : +31 (0) 165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T : +44 (0)1914 113 146  
F : +44 (0)1914 113 147  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T : +33(0) 130 40 00 44  
F : +33(0) 130 40 99 80  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T : +32 (0) 13 460 200  
F : +32 (0) 13 460 201  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)