

**PROCHEMKO**



## SARDEX GREEN

# Removes atmospheric fouling, rust, salts, and lime deposits

- Effective cleaner for surfaces made of concrete, concrete blocks, and bricks
- Descaling agent and rust remover
- Extremely fast action
- Does not contain hydrochloric acid
- Biodegradable

# SARDEX GREEN

## DESCRIPTION

A highly-concentrated liquid acid cleaner based on modified organic acids for mineral construction materials, such as concrete blocks, brick, and mineral plasters; also usable as a descaler and rust dissolver.

## RECOMMENDED USE

Sardex Green is suitable for removing atmospheric fouling, rust, and salt efflorescence from masonry and concrete, and a variety of types natural stone.  
Also suitable for removing limescale in showers, toilets, saunas and on tiles.

## PRACTICAL CONSUMPTION

Consumption is greatly dependent on the amount of dirt, dilution, and type of surface.

## DIRECTIONS FOR USE

Wet the surface with water.  
Dilute Sardex Green with water maximally to a ratio of 1:5.  
Apply the product using a brush, cloth, or brush.  
Let the product soak in for about 20 to 30 minutes.  
Rinse off thoroughly with water.

## APPLICATION CONDITIONS

Minimum ambient temperature : 5 °C  
Maximum relative humidity : 100%  
Minimum surface temperature : 5 °C  
Maximum surface temperature: 35 °C

## CLEANING OF EQUIPMENT / SPILLS

Rinse with clean water immediately after use.

## REMARKS

Dispose of remnants of the product and empty packaging as chemical waste in accordance with the local regulations and legal requirements.

## PH

1

## SHELF LIFE

Can be kept for a minimum of 12 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

Date issued: 23/10/2025

**Available colours & pack sizes:** Please refer to the respective product page on [www.rust-oleum.eu](http://www.rust-oleum.eu) for an overview of actual available colours and pack sizes.

**Disclaimer:** The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from [www.rust-oleum.eu](http://www.rust-oleum.eu) or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T : +31 (0) 165 593 636  
F : +31 (0) 165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T : +44 (0)1914 113 146  
F : +44 (0)1914 113 147  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T : +33(0) 130 40 00 44  
F : +33(0) 130 40 99 80  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T : +32 (0) 13 460 200  
F : +32 (0) 13 460 201  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)