



## STICKER-EX

# Removes stickers and sticker remains

- Effective action and result
- For almost all surfaces
- Wide range of use
- Handy aerosol

# STICKER-EX

## DESCRIPTION

To remove stickers and sticker remains.  
Penetrates deep into the adhesive and dissolves it.  
Also suitable for the removal of rubber streaks (from car tyres and shoe soles), silicon residues, etc.

## RECOMMENDED USE

This agent removes stickers, adhesive residues, rubber streaks and glue, tape, tar splashes, silicon residues, uncured PUR, grease stains, oil, heel prints, tyre marks, and so on from almost all thick non-porous surfaces.

## THEORETICAL CONSUMPTION

4 – 15 m<sup>2</sup>/l

## PRACTICAL CONSUMPTION

The consumption is heavily dependent on the surface and type of label or sticker.

## DIRECTIONS FOR USE

Apply Sticker-Ex using the aerosol on the surface to be treated.  
Let it soak in for a few minutes depending on the weather conditions, surface, and type of sticker.  
Spray the adhesive remnants from removed stickers again and then remove with a cloth or paper.  
Scratch open plastic stickers and ordinary stickers with a waterproof finishing layer.  
If possible, rinse off the surface with plenty of water.  
Always test on a part of the surface to be treated to assess whether the product is compatible with the surface.

## APPLICATION CONDITIONS

Minimum ambient temperature : 5 °C  
Maximum relative humidity : 100%  
Minimum surface temperature : 5 °C  
Maximum surface temperature: 35 °C  
Low temperatures can slow down the working of the product.

## CLEANING OF EQUIPMENT / SPILLS

Rinse with water immediately after use.

## REMARKS

Dispose of the product residue, waste from removing graffiti, and empty packaging as chemical waste in accordance with the local regulations and legal provisions.

## PH

9.5000

## SHELF LIFE

Can be kept for a minimum of 12 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

Date issued: 07/06/2022

**Available colours & pack sizes:** Please refer to the respective product page on [www.rust-oleum.eu](http://www.rust-oleum.eu) for an overview of actual available colours and pack sizes.

**Disclaimer:** The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from [www.rust-oleum.eu](http://www.rust-oleum.eu) or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T : +31 (0) 165 593 636  
F : +31 (0) 165 593 600  
info@rust-oleum.eu

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T : +44 (0)1914 113 146  
F : +44 (0)1914 113 147  
info@rust-oleum.eu

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T : +33(0) 130 40 00 44  
F : +33(0) 130 40 99 80  
info@rust-oleum.eu

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T : +32 (0) 13 460 200  
F : +32 (0) 13 460 201  
info@rust-oleum.eu