



STO-NEX 1

Water-dispersed mineral floor impregnation

- Penetrates deep into the surface to be treated
- Water-based product
- Strong grease and oil repellence
- Hardly visible
- No impact on anti-slip properties

STO-NEX 1

DESCRIPTION

An almost invisible hydrophobic and oleophobic agent based on fluorinated polymers and acrylates and protecting porous stone and stone-like surfaces.

RECOMMENDED USE

Sto-Nex 1 is used to protect natural stone such as: sandstone, terrazzo, limestone, blue stone, granite etc.

THEORETICAL CONSUMPTION

10 - 20 m²/l

PRACTICAL CONSUMPTION

Consumption depends heavily on the surface's rate of absorbency.

DIRECTIONS FOR USE

Shake Sto-Nex 1 before use. Use this product as supplied. Apply the product in a single layer, taking care that the entire surface is drenched, but avoiding a residue on the surface. Use a (wide) brush or soaper. Take care that the apparatus is free of detergents. Make clean and dry, and remove grease. Avoid leaving a residue of chemicals from cleaning.

APPLICATION CONDITIONS

Minimum ambient temperature: 5°C

Maximum relative humidity: 100%

Minimum surface temperature: 5°C

Maximum surface temperature: 35°C

CLEANING OF EQUIPMENT / SPILLS

Rinse with clean water directly after use.

REMARKS

Dispose of remaining product and empty packaging as chemical waste, in accordance with the local regulations and legal requirements.

PH

7

SHELF LIFE

Minimum of 12 months when stored in a dry, cool and frost-free environment in the original, unopened packaging.

Date issued: 05/02/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu