



STO-NEX 4

Floor impregnation with colour enhancing effect

- Penetrates deep into the surface to be treated
- Beautiful 'wet look' improves the appearance of weathered stone
- Highly grease and oil repellent
- Ideal for natural stone
- Does not affect anti-slip properties

STO-NEX 4

DESCRIPTION

A hydrophobic and oleophobic agent based on alcohols that protects porous stone and stony surfaces and provides a wet look.

RECOMMENDED USE

Sto-Nex 4 is used to protect natural stone, such as sandstone, terrazzo, limestone, blue stone, granite etc.

DRY TIMES BY 20° C/RH 50%

Touch dry:	N/A
Dry to recoat:	N/A
Fully cured:	N/A

PRACTICAL CONSUMPTION

Consumption is heavily dependent on the absorptive capacity of the surface.

DIRECTIONS FOR USE

Degrease, clean, and dry the surface.
Avoid leaving cleaning chemicals residues.
Shake Sto-nex 4 before use.
Use this product as supplied.
Apply the product wet in one layer and ensure the surface is saturated.
Avoid over saturating.
Use a (wide) brush or squeegee.
Use a clean and grease-free tool.

APPLICATION CONDITIONS

Minimum ambient temperature : 5 °C
Maximum relative humidity : 80%
Minimum surface temperature : 5 °C
Maximum surface temperature: 30 °C

CLEANING OF EQUIPMENT / SPILLS

Rinse with Isopropyl Alcohol immediately after use.

REMARKS

Dispose of remnants of the product and empty packaging as chemical waste in accordance with the local regulations and legal requirements.

SHELF LIFE

Can be kept for a minimum of 6 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

Date issued: 05/02/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu