

**PROCHEMKO**



## UNIVERSOL® PUMPSPRAY

# Protects and degreases paintwork and more

- Anti-static
- Do not wash afterwards
- Biodegradable
- Low foaming

[WWW.PROCHEMKO.EU](http://WWW.PROCHEMKO.EU)

# UNIVERSOL® PUMPSPRAY

## DESCRIPTION

For cleaning and degreasing surfaces to be painted and make the surfaces anti-static. Also highly suitable as a universal cleaner for cleaning slats, windows, floors, doors, carpets, gas cookers, frames, etc. Also removes nicotine stains.

## RECOMMENDED USE

Universol Pump Spray with a Ready to Use mixture is very suitable for degreasing surfaces to be painted and making the surfaces anti-static. The excellent properties of this product mean you do not have to wash the surface, such that you can immediately start painting. At the appropriate degree of dilution, it is suitable for cleaning floors, windows, engines, household appliances, etc.

## PRACTICAL CONSUMPTION

Dependent on the degree of dilution, the surface, and the degree of fouling.

## DIRECTIONS FOR USE

Universol Pump Spray is ready-to-use and should not be diluted any further. With heavy fouling, repeat treatments and facilitate the cleaning action using a white (non-woven) nylon pad. Before refilling the Universol spray bottle, dilute to the mixture ratio of 115 ml of Universol Concentrate to 385 ml of clean water. To prevent foam forming, first fill the bottle with water to the desired level, then add the Universol Concentrate.

## APPLICATION CONDITIONS

Can be used in all circumstances, but do not apply in direct sunlight or in frosty conditions.

## CLEANING OF EQUIPMENT / SPILLS

Rinse with water immediately after use.

## REMARKS

In case of use for cleaning very dark or bright acrylic decorative paints, a test on a small surface is recommended to check possible discoloration and deterioration.

## PH

9

## SHELF LIFE

Can be kept for a minimum of 12 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

Date issued: 05/02/2025

**Available colours & pack sizes:** Please refer to the respective product page on [www.rust-oleum.eu](http://www.rust-oleum.eu) for an overview of actual available colours and pack sizes.

**Disclaimer:** The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from [www.rust-oleum.eu](http://www.rust-oleum.eu) or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T : +31 (0) 165 593 636  
F : +31 (0) 165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T : +44 (0)1914 113 146  
F : +44 (0)1914 113 147  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T : +33(0) 130 40 00 44  
F : +33(0) 130 40 99 80  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T : +32 (0) 13 460 200  
F : +32 (0) 13 460 201  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)