

**PROCHEMKO**



## FINISHING SOLUTION

# Smooths out freshly caulked joints

- Suitable for almost all caulked joints
- Acid and alkali free
- For use indoors and outdoors
- Easily rinsed off with water

# FINISHING SOLUTION

## DESCRIPTION

A special tool to smooth freshly caulked joints for almost all types of sealants.

## RECOMMENDED USE

Used to level off joints filled with polysulphide, acrylic, silicone, and hybrid sealants.  
Used for joints in rubber, plastic, glass, bare metals and/or alloys, and stainless steel.

## THEORETICAL CONSUMPTION

10 – 20 m<sup>2</sup>/l

## DIRECTIONS FOR USE

Apply in accordance with the manufacturer/supplier instructions.  
One part Finishing Solution dilute maximally to 3 parts water.  
Apply with using a cloth, sponge, low pressure, or brush.  
Afterwards, smooth off the joints to the desired result.  
Afterwards, rinse/spray off with clean water.  
Note: Never allow the product to dry out.  
If necessary, repeat the treatment.

## APPLICATION CONDITIONS

Minimum ambient temperature : 10 °C  
Maximum relative humidity : 85%  
Minimum surface temperature : 10 °C  
Maximum surface temperature: 30 °C

## CLEANING OF EQUIPMENT / SPILLS

Rinse with water immediately after use.

## REMARKS

Dispose of remaining product and empty packaging as chemical waste in accordance with the local regulations and legal requirements.

## PH

7

## SHELF LIFE

Can be kept for a minimum of 12 months when stored in a dry, cool, and frost-free environment in the original unopened packaging.

Date issued: 05/02/2025

**Available colours & pack sizes:** Please refer to the respective product page on [www.rust-oleum.eu](http://www.rust-oleum.eu) for an overview of actual available colours and pack sizes.

**Disclaimer:** The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from [www.rust-oleum.eu](http://www.rust-oleum.eu) or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T : +31 (0) 165 593 636  
F : +31 (0) 165 593 600  
info@rust-oleum.eu

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T : +44 (0)1914 113 146  
F : +44 (0)1914 113 147  
info@rust-oleum.eu

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T : +33(0) 130 40 00 44  
F : +33(0) 130 40 99 80  
info@rust-oleum.eu

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T : +32 (0) 13 460 200  
F : +32 (0) 13 460 201  
info@rust-oleum.eu