



## WENDRO

# Highly powerful, strong alkaline facade cleaning paste

- Effective cleaning of mineral surfaces
- Ideal for acid-sensitive surfaces
- Removes atmospheric dirt, patina, grease, oil and paint
- Paste-like formula does not drip from the wall
- Free from carbon tetra chloride





# WENDRO

## DESCRIPTION

Extremely potent, strong alkaline facade cleaning paste based on lye, surfactants, special cleaning enhancers, evaporation inhibitors for cleaning acid-sensitive mineral surfaces.

## RECOMMENDED USE

Wendro is suitable for cleaning acid-sensitive, mineral surfaces, masonry, concrete, natural stone, etc.

## THEORETICAL CONSUMPTION

2 - 3 m<sup>2</sup>/kg

## PRACTICAL CONSUMPTION

Consumption depends heavily on the level of dirt and type of surface.

## DIRECTIONS FOR USE

- Protect alkali-sensitive areas
- Use Wendro as supplied
- Apply the product using a wide brush or hand brush
- Allow the product to work for a minimum of 30 minutes and a maximum of 36 hours
- Spray off with water under the appropriate pressure (water temperature max. 40 °C) until no more foaming occurs
- Check the pH of the surface, neutralising as required

NB: When much time is required for the product to take effect e.g. when removing paint, then we advise protecting Wendro from drying out by covering with a thin sheet of PE. After allowing to take effect first remove thick layers with a spatula before spraying off with water.

## APPLICATION CONDITIONS

Minimum ambient temperature: 5°C

Maximum relative humidity: 100%

Minimum surface temperature: 5°C

Maximum surface temperature: 35°C

## CLEANING OF EQUIPMENT / SPILLS

Rinse with clean water directly after use.

## REMARKS

Dispose of remaining product and empty packaging as chemical waste, in accordance with the local regulations and legal requirements.

## PH

14

## SHELF LIFE

Minimum of 12 months when stored in a dry, cool and frost-free environment in the original, unopened packaging.

Date issued: 05/02/2025

**Available colours & pack sizes:** Please refer to the respective product page on [www.rust-oleum.eu](http://www.rust-oleum.eu) for an overview of actual available colours and pack sizes.

**Disclaimer:** The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from [www.rust-oleum.eu](http://www.rust-oleum.eu) or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T : +31 (0) 165 593 636  
F : +31 (0) 165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T : +44 (0)1914 113 146  
F : +44 (0)1914 113 147  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T : +33(0) 130 40 00 44  
F : +33(0) 130 40 99 80  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T : +32 (0) 13 460 200  
F : +32 (0) 13 460 201  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)