

## SAFETY DATA SHEET

5301 EPOXY Shield ® MAXX (Activator)

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : 5301 EPOXY Shield ® MAXX (Activator)

Product description : Hardener.
Product type : Liquid.

**UFI** : 5J40-Y042-N00M-VCY8

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses	
Consumer use Industrial use Professional use	

Uses advised against	Reason
None identified.	-

#### 1.3 Details of the supplier of the safety data sheet

**RUST-OLEUM EUROPE** 

Martin Mathys NV, Kolenbergstraat 23, B-3545 Zelem, Belgium

Telephone no.: +32 (0) 13 460 200

Fax no.: +32 (0) 13 460 201

Tor Coatings Limited

Unit 21, White Rose Way, Follingsby Park, Gateshead, Tyne & Wear, NE10 8YX United Kingdom

Telephone no.: +44 (0) 191 4106611

Fax no.: +44 (0) 191 4920125 enquiries@tor-coatings.com

e-mail address of person : rpmeurohas@rustoleum.eu

responsible for this SDS

#### 1.4 Emergency telephone number

**National advisory body/Poison Centre** 

<u>Supplier</u>

**Telephone number** : +44 870 8200418 / +44 2038073798

Hours of operation : 24 / 7

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Muta. 2, H341

Aquatic Chronic 2, H411

Date of issue/Date of revision : 11/05/2021 Date of previous issue : 11/05/2021 Version : 5 1/16

#### SECTION 2: Hazards identification

The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms :







Signal word : Warning

**Hazard statements** : Causes skin irritation.

May cause an allergic skin reaction. Causes serious eye irritation. Suspected of causing genetic defects.

Toxic to aquatic life with long lasting effects.

**Precautionary statements** 

General: P103 - Read carefully and follow all instructions.

P102 - Keep out of reach of children.

P101 - If medical advice is needed, have product container or label at hand.

: P280 - Wear protective gloves, protective clothing and eye or face protection.

P273 - Avoid release to the environment.

Response : P391 - Collect spillage.
Storage : P405 - Store locked up.

Disposal : P501 - Dispose of contents and container in accordance with all local, regional,

: Contains epoxy constituents. May produce an allergic reaction.

national and international regulations.

**Hazardous ingredients** : 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

2,3-epoxypropyl o-tolyl ether

Supplemental label elements

**Prevention** 

Supplemental label elements: Detergents -

Regulation (EC) No

907/2006

: Not applicable.

: Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and

articles

**Special packaging requirements** 

Containers to be fitted with child-resistant

fastenings

: Not applicable.

Tactile warning of danger : Yes, applicable.

#### 2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do not result in classification

: None known.

Date of issue/Date of revision : 11/05/2021 Date of previous issue : 11/05/2021 Version : 5 2/16

5301 EPOXY Shield ® MAXX (Activator)

## **SECTION 3: Composition/information on ingredients**

3.2 Mixtures : Mixture

**United Kingdom: Great Britain** 

Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Type
2,2'-[(1-methylethylidene)bis (4,1-phenyleneoxymethylene)] bisoxirane	REACH #: 01-2119456619-26 EC: 216-823-5 CAS: 1675-54-3 Index: 603-073-00-2	≥75 - ≤90	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411	[1]
2-(propyloxy)ethanol	REACH #: 01-2119883539-19 EC: 220-548-6 CAS: 2807-30-9 Index: 603-095-00-2	≤10	Acute Tox. 4, H312 Eye Irrit. 2, H319	[1]
2,3-epoxypropyl o-tolyl ether	EC: 218-645-3 CAS: 2210-79-9 Index: 603-056-00-X	≤10	Skin Irrit. 2, H315 Skin Sens. 1, H317 Muta. 2, H341 Aquatic Chronic 2, H411	[1]
			See Section 16 for the full text of the H statements declared above.	

#### **Type**

- [1] Substance classified with a health or environmental hazard
- [2] Substance with a workplace exposure limit
- [3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII
- [4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII
- [5] Substance of equivalent concern
- [6] Additional disclosure due to company policy

[e] · · · · · · · · · · · · · · · · · · ·	
SCL (Specific Concentration Limits)	Not applicable
Not applicable.	Not applicable.
ATE (coute toxicity estimates)	
ATE (acute toxicity estimates)	
Not applicable.	Not applicable.
Nanoform Nanoform	
Particle characteristics	Particle Size
This product does not contains nanomaterials.	Not applicable.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Date of issue/Date of revision : 11/05/2021 Date of previous issue : 11/05/2021 Version : 5 3/16

Skin contact

## **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

**Eye contact**: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower

eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10

minutes. Get medical attention.

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If

not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately.

Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Wash with plenty of soap and water. Remove contaminated clothing and shoes.

Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse.

Clean shoes thoroughly before reuse.

Ingestion : Wash out mouth with water. Remove dentures if any. If material has been

swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open

airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It

may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

### 4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

**Eye contact** : Adverse symptoms may include the following:

pain or irritation watering

Inhalation : No specific data.

**Skin contact**: Adverse symptoms may include the following:

irritation redness

redness

**Ingestion**: No specific data.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

**Specific treatments**: No specific treatment.

## **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

**Unsuitable extinguishing** 

media

: None known.

#### 5.2 Special hazards arising from the substance or mixture

Date of issue/Date of revision : 11/05/2021 Date of previous issue : 11/05/2021 Version : 5 4/16

5301 EPOXY Shield ® MAXX (Activator)

## **SECTION 5: Firefighting measures**

Hazards from the substance or mixture : In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Hazardous combustion** products

: Decomposition products may include the following materials: carbon dioxide carbon monoxide

#### 5.3 Advice for firefighters

**Special protective actions** for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

**Special protective** equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

**Additional information** 

: No unusual hazard if involved in a fire.

#### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

#### 6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

#### 6.3 Methods and material for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

#### Large spill

: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product.

#### 6.4 Reference to other sections

: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

Date of issue/Date of revision : 11/05/2021 Date of previous issue : 11/05/2021 Version : 5 5/16

## **SECTION 7: Handling and storage**

The information in this section contains generic advice and guidance.

#### 7.1 Precautions for safe handling

#### **Protective measures**

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid breathing vapour or mist. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

## Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

#### 7.2 Conditions for safe storage, including any incompatibilities

Do not store above the following temperature: 35°C (95°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

#### **Seveso Directive - Reporting thresholds**

#### **Danger criteria**

	Notification and MAPP threshold	Safety report threshold	
E2	200 tonne	500 tonne	

#### 7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific : Not available.

solutions

## **SECTION 8: Exposure controls/personal protection**

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

#### 8.1 Control parameters

#### **Occupational exposure limits**

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance

Date of issue/Date of revision : 11/05/2021 Date of previous issue : 11/05/2021 Version : 5 6/16

## SECTION 8: Exposure controls/personal protection

documents for methods for the determination of hazardous substances will also be required.

#### **DNELs/DMELs**

No DNELs/DMELs available.

#### **PNECs**

No PNECs available

#### 8.2 Exposure controls

## Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

#### Individual protection measures

#### **Hygiene measures**

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### **Eye/face protection**

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. Use eye protection according to EN 166. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

#### **Skin protection**

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

#### **Hand protection**

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. > 8 hours (breakthrough time): polyvinyl alcohol (PVA) (EN 374).

The recommendation for the type or types of glove to use when handling this product is based on information from the following source: EN374. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

#### **Body protection**

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Wear overalls or long sleeved shirt.

#### Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Date of issue/Date of revision : 11/05/2021 Date of previous issue : 11/05/2021 Version : 5 7/16

## **SECTION 8: Exposure controls/personal protection**

**Respiratory protection** 

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: In case of insufficient ventilation, wear suitable respiratory equipment. Recommended: organic vapour filter (Type A) (EN 140).

**Environmental exposure** controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

#### 9.1 Information on basic physical and chemical properties

Physical state : Liquid. [Thick, oily liquid.]

Colour : Not available.

**Odour** Bland

**Odour threshold** : Not available.

Melting point/freezing point

Initial boiling point and boiling

range

: <0°C

: >200°C (>392°F) [Literature]

Flammability (solid, gas)

Slightly flammable in the presence of the following materials or conditions: open

flames, sparks and static discharge.

Non-flammable but will burn on prolonged exposure to flame or high

temperature.

Upper/lower flammability or

explosive limits

: Not available.

Flash point

: Closed cup: >130°C (>266°F) [ISO EN 2719 / DIN 51758 / ASTM D93]

**Auto-ignition temperature** 

: Not available.

**Decomposition temperature** 

Not applicable.

pН pH: Justification

: Product is non-polar/aprotic. : Dynamic: Not applicable.

: >400°C (>752°F) [Literature]

Solubility(ies)

**Viscosity** 

: Partially soluble in the following materials: acetone.

Solubility in water Partition coefficient: n-octanol/ : Not applicable.

water

: Not available.

Vapour pressure : <0,013 kPa (<0,1 mm Hg) [calculated.]

**Evaporation rate** : <1 (ether (anhydrous) = 1)

**Relative density** : 1,13 [calculated.]

: 1,13 g/cm3 [20°C (68°F)] [calculated.] **Density** 

Vapour density : >1 [Air = 1]

**Explosive properties** : No unusual hazard if involved in a fire.

**Oxidising properties** : Not available.

**Particle characteristics** 

Median particle size : Not applicable.

Date of issue/Date of revision : 11/05/2021 Date of previous issue : 11/05/2021 Version 8/16

5301 EPOXY Shield ® MAXX (Activator)

### SECTION 10: Stability and reactivity

10.1 ReactivityNo specific test data related to reactivity available for this product or its ingredients.

**10.2 Chemical stability** : The product is stable.

10.3 Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**10.4 Conditions to avoid** : No specific data.

10.5 Incompatible materials : No specific data.

10.6 Hazardous decomposition products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

## **SECTION 11: Toxicological information**

## 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
2,2'-[(1-methylethylidene)bis (4,1-phenyleneoxymethylene)] bisoxirane	LD50 Dermal	Rabbit	20 g/kg	-
2-(propyloxy)ethanol 2,3-epoxypropyl o-tolyl ether	LD50 Oral LC50 Inhalation Dusts and mists LD50 Oral	Rat Rat Rat	3089 mg/kg 6090 mg/m³ 4 g/kg	- 4 hours -

**Conclusion/Summary**: Based on available data, the classification criteria are not met.

#### **Acute toxicity estimates**

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
2,2'-[(1-methylethylidene)bis	N/A	20000	N/A	N/A	N/A
(4,1-phenyleneoxymethylene)]bisoxirane					
2-(propyloxy)ethanol	3089	1100	N/A	N/A	N/A
2,3-epoxypropyl o-tolyl ether	4000	N/A	N/A	N/A	6,09

#### **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
2,2'-[(1-methylethylidene)bis (4,1-phenyleneoxymethylene)] bisoxirane	Eyes - Severe irritant	Rabbit	-	24 hours 2 milligrams	-
	Skin - Mild irritant	Rabbit	-	500 milligrams	-
2-(propyloxy)ethanol	Eyes - Severe irritant	Rabbit	-	24 hours 750 Micrograms	-
	Eyes - Severe irritant	Rabbit	-	100 milligrams	-
	Skin - Mild irritant	Guinea pig	-	500 milligrams	-
	Skin - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
2,3-epoxypropyl o-tolyl ether	Skin - Severe irritant	Rabbit	-	24 hours 500 microliters	-

#### **Conclusion/Summary**

Date of issue/Date of revision : 11/05/2021 Date of previous issue : 11/05/2021 Version : 5 9/16

5301 EPOXY Shield ® MAXX (Activator)

## **SECTION 11: Toxicological information**

Skin : Causes skin irritation.

**Eves** Causes serious eve irritation.

: Based on available data, the classification criteria are not met. Respiratory

**Sensitisation** 

Product/ingredient name	Route of exposure	Species	Result
2,2'-[(1-methylethylidene)bis (4,1-phenyleneoxymethylene)] bisoxirane	skin	Mouse	Sensitising
2,3-epoxypropyl o-tolyl ether	skin skin	Guinea pig Guinea pig	Sensitising Sensitising

**Conclusion/Summary** 

Skin : May cause an allergic skin reaction.

: Based on available data, the classification criteria are not met. Respiratory

**Mutagenicity** 

**Conclusion/Summary** : Suspected of causing genetic defects.

**Carcinogenicity** 

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

**Reproductive toxicity** 

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

**Teratogenicity** 

Product/ingredient name	Result	Species	Dose	Exposure
2,2'-[(1-methylethylidene)bis (4,1-phenyleneoxymethylene)] bisoxirane	Positive - Dermal	Rabbit	300 mg/kg	1 days per week
	Positive - Oral Positive - Oral	Rat Rabbit	180 mg/kg 180 mg/kg	1 days per week 1 days per week

**Conclusion/Summary** : Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

**Aspiration hazard** 

Not available.

: Routes of entry anticipated: Oral, Dermal. Information on likely routes of exposure

Routes of entry not anticipated: Inhalation.

Potential acute health effects

**Eye contact** : Causes serious eye irritation.

Inhalation No known significant effects or critical hazards.

: Causes skin irritation. May cause an allergic skin reaction. **Skin contact** 

Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** : Adverse symptoms may include the following:

> pain or irritation watering

redness

Inhalation : No specific data.

Date of issue/Date of revision : 11/05/2021 Date of previous issue : 11/05/2021 Version 10/16

5301 EPOXY Shield ® MAXX (Activator)

## **SECTION 11: Toxicological information**

**Skin contact** : Adverse symptoms may include the following:

irritation redness

**Ingestion**: No specific data.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Short term exposure** 

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate

: Not available.

effects

Potential delayed effects : Not available.

#### Potential chronic health effects

Not available.

**Conclusion/Summary**: Based on available data, the classification criteria are not met.

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed to

very low levels.

**Carcinogenicity** : No known significant effects or critical hazards.

Mutagenicity : Suspected of causing genetic defects.

**Reproductive toxicity**: No known significant effects or critical hazards.

**Endocrine disrupting** 

properties

: Not available.

Other information : Not available

## **SECTION 12: Ecological information**

#### 12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
2-(propyloxy)ethanol	Acute LC50 >5000 mg/l	Daphnia spec.	48 hours
	Acute LC50 >1000 mg/l	Fish	96 hours
2,3-epoxypropyl o-tolyl ether	Acute EC50 1 to 10 mg/l	Daphnia spec Daphnia magna	24 hours
	Acute IC50 >100 mg/l	Bacteria	3 hours
	Acute LC50 1 to 10 mg/l	Fish	96 hours
	Acute LC50 131 mg/l	Fish	96 hours

**Conclusion/Summary**: Toxic to aquatic life with long lasting effects.

#### 12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
2,2'-[(1-methylethylidene)bis (4,1-phenyleneoxymethylene)] bisoxirane		6 to 12 % - Not readily - 28 days	-	-
2,3-epoxypropyl o-tolyl ether	OECD 301B	3 to 4 % - Not readily - 28 days	-	-

**Conclusion/Summary**: This product has not been tested for biodegradation.

Date of issue/Date of revision : 11/05/2021 Date of previous issue : 11/05/2021 Version : 5 11/16

5301 EPOXY Shield ® MAXX (Activator)

## **SECTION 12: Ecological information**

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
2,2'-[(1-methylethylidene)bis	-	-	Not readily
(4,1-phenyleneoxymethylene)]			
bisoxirane			
2-(propyloxy)ethanol	-	-	Readily
2,3-epoxypropyl o-tolyl ether	-	-	Not readily

#### 12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
2,2'-[(1-methylethylidene)bis (4,1-phenyleneoxymethylene)] bisoxirane	-,-	3 to 31	low
2-(propyloxy)ethanol 2,3-epoxypropyl o-tolyl ether	0,673 >3		low low

#### 12.4 Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Mobility : Not available.

#### 12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting

properties

: No known significant effects or critical hazards.

**12.7 Other adverse effects** : No known significant effects or critical hazards.

## **SECTION 13: Disposal considerations**

The information in this section contains generic advice and guidance.

#### 13.1 Waste treatment methods

#### **Product**

**Methods of disposal** 

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes. European waste catalogue (EWC)

Waste code	Waste designation
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances

#### **Special precautions**

: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Date of issue/Date of revision : 11/05/2021 Date of previous issue : 11/05/2021 Version : 5 12/16

## **SECTION 14: Transport information**

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	UN3082	UN3082	UN3082	UN3082
14.2 UN proper shipping name	Environmentally hazardous substance, liquid, n.o.s. (2,2'-[ (1-methylethylidene)bis (4,1-phenyleneoxymethylene)] bisoxirane)	Environmentally hazardous substance, liquid, n.o.s. (2,2'-[ (1-methylethylidene)bis (4,1-phenyleneoxymethylene)] bisoxirane)	Environmentally hazardous substance, liquid, n.o.s Marine pollutant (2,2'-[ (1-methylethylidene)bis (4,1-phenyleneoxymethylene)] bisoxirane)	Environmentally hazardous substance, liquid, n.o.s. (2,2'-[ (1-methylethylidene)bis (4,1-phenyleneoxymethylene)] bisoxirane)
14.3 Transport hazard class(es)	9	9	9	9
14.4 Packing group	III	III	III	III
14.5 Environmental hazards	Yes.	Yes.	Yes.	Yes.
Additional information	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.  Tunnel code (-)	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.  Emergency schedules F-A; S-F	This product is not regulated as a dangerous good when transported in sizes of ≤5 L or ≤5 kg, provided the packagings meet the general provisions of 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.  Quantity limitation Passenger and Cargo Aircraft: 450 L. Packaging instructions: 964. Cargo Aircraft Only: 450 L. Packaging instructions: 964. Limited Quantities - Passenger Aircraft: 30 kg. Packaging instructions: Y964.

14.6 Special precautions for user

: **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments

: Not available.

Date of issue/Date of revision : 11/05/2021 Date of previous issue : 11/05/2021 Version : 5 13/16

5301 EPOXY Shield ® MAXX (Activator)

## **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU Regulation (EC) No. 1907/2006 (REACH)

Annex XIV - List of substances subject to authorisation

**Annex XIV** 

None of the components are listed.

Substances of very high concern

None of the components are listed.

Annex XVII - Restrictions on the manufacture,

: Not applicable.

placing on the market and use of certain dangerous substances, mixtures and

articles

**Other EU regulations** 

VOC

VOC for Ready-for-Use Mixture

: IIA/j. Two-pack reactive performance coatings for specific end use such as floors. EU

limit value for this product: 140g/l (2010.)

This product contains a maximum of 53 g/l VOC.

Industrial emissions (integrated pollution prevention and control) -

Air

: Not listed

: Not listed

Industrial emissions (integrated pollution prevention and control) -

Water

Ozone depleting substances (1005/2009/EC)

Not listed.

Prior Informed Consent (PIC) (649/2012/EC)

Not listed.

Persistent Organic Pollutants (850/2004/EC)

Not listed.

**Seveso Directive** 

This product is controlled under the Seveso Directive.

**Danger criteria** 

Category

E2

**United Kingdom: Great Britain** 

References : EH40/2005 Workplace exposure limits

Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by

Regulation (EU) No. 2020/878

REGULATION (EU) 2016/425 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 9 March 2016 on personal protective equipment and repealing Council

Directive 89/686/EEC

International regulations

**Stockholm Convention on Persistent Organic Pollutants** 

List name	Ingredient name	Status
Not listed.		

#### **Rotterdam Convention on Prior Informed Consent (PIC)**

Date of issue/Date of revision : 11/05/2021 Date of previous issue : 11/05/2021 Version : 5 14/16

5301 EPOXY Shield ® MAXX (Activator)

## SECTION 15: Regulatory information

Not listed.

#### **UNECE Aarhus Protocol on POPs and Heavy Metals**

List name	Ingredient name	Status
Not listed.		

**CN** code : 3208 90 91 00

**Inventory list** 

**Australia** : All components are listed or exempted. Canada : All components are listed or exempted. China : All components are listed or exempted. : All components are listed or exempted. **Europe** 

Japan inventory (CSCL): All components are listed or exempted. **Japan** 

Japan inventory (ISHL): Not determined.

**New Zealand** : At least one component is not listed. **Philippines** : All components are listed or exempted. Republic of Korea : All components are listed or exempted. **Taiwan** : All components are listed or exempted.

**Thailand** : Not determined. **Turkey** : Not determined. **United States** Not determined. **Viet Nam** : Not determined.

15.2 Chemical safety

assessment

: This product contains substances for which Chemical Safety Assessments are still

required.

## **SECTION 16: Other information**

Indicates information that has changed from previously issued version.

**Abbreviations and acronyms**: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/20081

DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

N/A = Not available

PBT = Persistent. Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration

RRN = REACH Registration Number

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

#### Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Skin Irrit. 2, H315	Expert judgment
Eye Irrit. 2, H319	Expert judgment
Skin Sens. 1, H317	Expert judgment
Muta. 2, H341	Expert judgment
Aquatic Chronic 2, H411	Expert judgment

Full text of abbreviated H statements

**United Kingdom: Great Britain** 

Date of issue/Date of revision : 11/05/2021 Date of previous issue : 11/05/2021 Version : 5 15/16

5301 EPOXY Shield ® MAXX (Activator)

#### **SECTION 16: Other information**

Full text of abbreviated	Н
statements	

H312 Harmful in contact with skin.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H341 Suspected of causing genetic defects.
H411 Toxic to aquatic life with long lasting effects.

## Full text of classifications [CLP/GHS]

Acute Tox. 4 ACUTE TOXICITY - Category 4
Aquatic LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2
Chronic 2
Eye Irrit. 2 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2
Muta. 2 GERM CELL MUTAGENICITY - Category 2
Skin Irrit. 2 SKIN CORROSION/IRRITATION - Category 2
Skin Sens. 1 SKIN SENSITISATION - Category 1

Date of printing
Date of issue/ Date of

revision

Date of previous issue : 1

: 21/05/2021

: 11/05/2021

Version : !

**Notice to reader** 

: 11/05/2021 : 5

IMPORTANT NOTE: The information in this Safety Data Sheet is based on the present state of knowledge and current legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates. Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this safety data sheet, then the user uses the product at their own risk.

MANUFACTURER'S DISCLAIMER: the conditions, methods and factors affecting the handling, storage, application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage, use and disposal are the responsibility of the users. Users must comply with all applicable health and safety laws.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot quarantee that these are the only hazards that exist.